NHL STENDEN
computer vision & data science

Computer Vision

Fourier Transform

10 April 2018

j.van.de.loosdrecht@nhl.nl, jaap@vdlmv.nl

Fourier Transform (FT)

- Introduction
- Applications
  - Finding periodic structures
  - Convolution theorem
  - Removing defocus and motion blur (deconvolution)
  - Correlation
  - Calculation of sharpness in the image

Fourier Transform

- Introduction
  - Frequency
  - Fourier analysis
  - 1D Fourier transform
  - Complex numbers
  - 2D Fourier transform
  - Displaying FT of images
  - Some examples of synthetic images
  - Interpreting the frequency domain
  - Demonstration image shift (*)
  - Demonstration exchange of magnitude and phase (*)

Frequency



low

middle

high

Fourier analysis

Every periodic signal can be written as a summation of a series of sine shaped signals with an increasing frequency:

- **DC component (harmonic 0)**
- **h1 * harmonic 1 (base frequency)**
- **h2 * harmonic 2 (2 x base frequency)**
- **h3 * harmonic 3**
  ….
- **hn * harmonic n**

27-aug-18 Fourier Transform 5

Fourier analysis of block wave

A block wave can be approximated with:

$$f(x) = \frac{h}{2} + \frac{2*h}{\pi}\left(\frac{\sin(x)}{1} + \frac{\sin(3x)}{3} + \frac{\sin(5x)}{5} + ...\right)$$

Where the block wave has an amplitude of h and a period of 2π.

27-aug-18 Fourier Transform 6

Block wave approximation



27-aug-18 Fourier Transform 7

Block wave approximation



27-aug-18 Fourier Transform 8

Block wave approximation



27-aug-18 Fourier Transform 9

Block wave approximation



27-aug-18 Fourier Transform 10

Block wave approximation



27-aug-18 Fourier Transform 11

Fourier analysis

Time domain

Fourier Transform

Inverse Fourier Transform

Frequency domain



27-aug-18 Fourier Transform 12

Fourier analysis

Example:

by analyzing the noise of a machine, anti-noise can be generated by inverting the phase of the noise

1D Fourier transform

Fourier transform

$$FT(u) = \int_{-\infty}^{+\infty} f(x) e^{-2\pi i u x} dx$$

Inverse Fourier transform

$$f(x) = \int_{-\infty}^{+\infty} FT(u) e^{2\pi i u x} du$$

$$e^{-2\pi i u x} = \cos(2\pi u x) - i \sin(2\pi u x)$$

$$i = \sqrt{-1}$$

Fast Fourier Transform (FFT): fast implementation for signals with a length of a power of two

2D Fourier transform

Images:

- **are 2D signals**
- **are interpreted as continuous signals**



Complex numbers

Cartesian representation
c = x + i y, where x and y are real numbers

- **x: real part**
- **y: imaginary part**

Polar representation

- **r: magnitude (amplitude)**
- **phi: phase (angle)**



Typical framework for FT operations



27-aug-18 Fourier Transform 17

Demonstration FT

- Open image circles.jls
- ***Zoom 256 256 BilinearPixelInterpolation***
- convert ComplexDoubleImage
- Show with edit convert image that pixels are complex numbers with imaginary part = 0
- FT complex image and use display LUT FloatLog
- Analyse edit result
- Perform the inverse FT on FT image
- Analyse edit result = almost original image (some rounding errors)

27-aug-18 Fourier Transform 18

Convert to ComplexDouble image



27-aug-18 Fourier Transform 19

FT of circles



27-aug-18 Fourier Transform 20

FT of circles



Inverse FT



Displaying complex images

In VisionLab the power spectrum of a complex image is displayed

The power spectrum is the square of the magnitude

The power spectrum of the FT of an image is symmetric to the origin and has often a high dynamical range

There are two display LUT's:

- **FloatLog**
- **FloatLinear**

Demonstration sinus patterns

- **Open script fftd1_2.jls**
- **Execute first part to generate a vertical sinus pattern and its FT,**
  note: direction in frequency domain (FT) is perpendicular to direction in space domain
- **Continue script for second part in order to generate a vertical sinus pattern with a lower frequency and its FT,**
  note: maxima in frequency domain are closer to the origin
- **Continue script for third part in order to generate a vertical sinus pattern with is 45 degrees rotated and its FT,**
  note: maxima frequency domain are perpendicular to patterns in space domain
- **Continue script for fourth part in order to generate a 2D sinus pattern and its FT**

Vertical sinus pattern



Vertical sinus pattern with a lower frequency



Sinus pattern is rotated 45 degrees



27-aug-18 Fourier Transform 27

2D sinus pattern



27-aug-18 Fourier Transform 28

Demonstration block patterns

- Open script fft_b.jls
- Execute first part to generate a vertical block pattern and its FT,
  note: only odd frequencies are present in frequency domain
- Execute second part to generate a vertical block pattern with a higher frequency and its FT,
  note: peaks in frequency domain have a bigger distance
- Execute third part to generate a 2D block pattern and its FT

Vertical block pattern



Vertical block pattern with a higher frequency



27-aug-18 Fourier Transform 31

2D block pattern



27-aug-18 Fourier Transform 32

Interpreting the power spectrum

Frequencies increase from the origin



27-aug-18 Fourier Transform 33

Interpreting the frequency domain

It is not easy possible to interpret the Cartesian representation.

Some interpretation can be given in the Polar representation:

- **The magnitude information gives information on the frequencies of the periodic structures contained in the image**
- **The phase information contains information about the position of those structures**

The power spectrum (square of the magnitude) gives the distribution of the energy of the frequencies in the image

27-aug-18 Fourier Transform 34

Demonstration image shift (*)

- Use script fft_pshift.jls
  - image circles.jl is cyclic shifted 8 pixels to the right
  - Original and shifted are Fourier transformed
  - Compare magnitudes of both transformed images
  - Compare phases of both transformed images

27-aug-18 Fourier Transform 35

Differences in magnitudes (*)



27-aug-18 Fourier Transform 36

Differences in phase (*)



Demonstration exchange of magnitude and phase (*)

- Use script fft_phase.jls
  - Image circles.jl is Fourier transformed
  - Image text.jl is Fourier transformed
  - Generate for both transformed images an image with magnitude information and an image with phase information
  - A complex image with magnitude information from circles and phase information from text is created
  - A complex image with phase information from circles and magnitude information from text is created
  - Both new complex image are inversed Fourier transformed
- Conclusion the phase information determines the content of the image

Demonstration exchange of magnitude and phase (*)



27-aug-18 Fourier Transform 39

Applications of Fourier transform

- **Applications:**
  - **Finding periodic structures**
    - **Low and high pass filter**
    - **Band reject filter**
  - **Convolution**
  - **Removing defocus and motion blur (deconvolution)**
  - **Correlation**

27-aug-18 Fourier Transform 40

Demonstration low and high pass filter

- Use script fft_filter.jls
  - Image circles.jl is Fourier transformed
  - Ideal low pass filter:
    - A circular mask image is created and multiplied with Fourier transform, this means that only the low frequencies are selected
    - Result is inversed Fourier transformed, note artifacts in image due to ideal (theoretical) low pass filter
  - Practical low pass filter:
    - A 'soft' circular mask with a Gaussian distribution is created and multiplied with Fourier transform, this means that only the low frequencies are selected
    - Result is inversed Fourier transformed and shows only the low frequencies
  - High pass filter:
    - A mask for the high pass filter is created and multiplied with Fourier transform, this means that the low frequencies are blocked
    - Result is inversed Fourier transformed and shows only the high frequencies

27-aug-18 Fourier Transform 41

Image circles.jl and it's FT



27-aug-18 Fourier Transform 42

A circular mask image is created and multiplied with Fourier transform



27-aug-18 Fourier Transform 43

Result of ideal low pass filter



27-aug-18 Fourier Transform 44

A 'soft' circular mask image is created and multiplied with Fourier transform



27-aug-18 Fourier Transform 45

Result of Gaussian low pass filter



27-aug-18 Fourier Transform 46

Mask for high pass filter



27-aug-18 Fourier Transform 47

Result of high pass filter



27-aug-18 Fourier Transform 48

Demonstration band reject filter

Purpose is to demonstrate how periodic structures (interference) can be removed from an image

- Use script fft_bandreject.jls
  - A distorted image circles.jl is created by adding a 45 degrees rotated sinus pattern. The distorted image is Fourier transformed.
  - The magnitude information is extracted and the positions of the maxima is searched for
  - A filter image with small Gaussian circles is created on the position of the maxima, note: the higher order components are not selected !
  - The filter image is inverted because the frequencies must be blocked
  - Inverted filter is multiplied with FT
  - Result is inversed FTed, note still artefacts in image, result is not perfect at the borders, due to high order components

27-aug-18 Fourier Transform 49

Distorted image and it's FT



27-aug-18 Fourier Transform 50

Search for the maxima



27-aug-18 Fourier Transform 51

Filter image with small Gausian circles



27-aug-18 Fourier Transform 52

Inverted filter image



27-aug-18 Fourier Transform 53

Inverted filter is multiplied with FT



27-aug-18 Fourier Transform 54

Inverse FT



Animation Fourier Transform

- **Open script FourierAnimation.jls**



Convolution theorem

Notation:

$\otimes = \text{convolution}$

- **Spatial domain**
  $image \otimes mask = convoluted\_image$
- **Frequency domain**
  $FT(image) * FT(mask) = FT(convoluted\_image)$
- **Convolution using FT**
  $convoluted\_image = FT^{inv}(FT(image) * FT(mask))$

27-aug-18 Fourier Transform 57

Convolution theorem



27-aug-18 Fourier Transform 58

Convolution theorem

A convolution in the spatial domain is exactly equivalent to a multiplication in the frequency domain.

If the kernel is smaller then the image, it is padded with zeroes to the full image size.
(some round off errors at the borders)

Demonstration Convolution theorem

- **Use script fft_conv.jls**
  - **Image circles.jl and it's FT**
  - **A point spread function (psf) mask is created and it's FT**
  - **FT 's are multiplied and result is reversed FT,**
    note similar result as convolution in spatial domain with a big smoothing mask
  - **Note: the differences with the example of script fft_filter.jls:**
    - **in fft_conv.jls the FT of psf is multiplied with FT of image.**
    - **in script fft_filter.jls a disk shape is multiplied with the FT of image**

Image circles and it's FT



27-aug-18 Fourier Transform 61

psf mask and it's FT



27-aug-18 Fourier Transform 62

FT 's are multiplied and result is reversed FT



27-aug-18 Fourier Transform 63

Removing defocus blur (deconvolution)

Notation:

$\otimes = \text{convolution}$

$FT_{image} = FT(image)$

Making unsharp:

- **Spatial domain**

  $\text{image} \otimes \text{psf} = \text{blurr}$

- **Frequency domain**

  $\text{FT}_{\text{image}} \times \text{FT}_{\text{psf}} = \text{FT}_{\text{blurr}}$

27-aug-18 Fourier Transform 64

Removing defocus blur (deconvolution)

Making unsharp image sharp in frequency domain:

$$\frac{FT_{blurr}}{FT_{psf}} = FT_{image}$$

But FT_{psf} contains complex zeroes:

$$\frac{FT_{blurr}}{FT_{psf}} = \frac{FT_{blurr}}{FT_{psf}} \times \frac{\overline{FT_{psf}}}{\overline{FT_{psf}}} = \frac{FT_{blurr} \times \overline{FT_{psf}}}{FT_{psf} \times \overline{FT_{psf}}} = \frac{FT_{blurr} \times \overline{FT_{psf}}}{\left|FT_{psf}\right|^2}$$

Divider is now a real, but still can be zero

27-aug-18 Fourier Transform 65

Wiener filter

Idea: add a small constant to the divider

$$\frac{FT_{blurr}}{FT_{psf}} = \frac{FT_{blurr} \times \overline{FT_{psf}}}{\left|FT_{psf}\right|^2 + k}$$

27-aug-18 Fourier Transform 66

Demonstration deconvolution

- Use script blurr.jls
  - lread blurr blurr.jl
  - display blurr
  - copy blurr psf
  - diskshape psf 128 128 8 1
  - display psf
  - copy blurr res
  - deconvolution res psf 0.01 // Wiener filter
  - display res
- Notes:
  - Result is not perfect
  - Parameters to tune: size of psf and estimate for k
  - Image restoration is a special branch of science and outside of scope of this course

Deconvolution



Exercise removing motion blur

- Use image motion_blur.jl
- Try to remove the motion blur
- Hint: use script blurr.jls as template and determine suitable point spread function

Answer: motion_blur.jls

27-aug-18 Fourier Transform 69

Correlation

Purpose: finding a specified pattern in an image

Idea: pattern is used as 'convolution mask', everywhere where the pattern fits to the image it will give a high convolution result

Theory:
find the peaks in $\mathrm{FT}^{\mathrm{inv}}(\mathrm{FT}_{\mathrm{image}} \times \overline{\mathrm{FT}_{\mathrm{pattern}}})$

Note: can not handle rotation and / or scaling

27-aug-18 Fourier Transform 70

Demonstration correlation

- Use script correlation.jls
  - Open image correlation.jl and select pattern
  - Add border to search pattern with average gray value
  - Correlate image with search pattern
  - Threshold on peaks of correlation
  - Map search result on original image,
    Notes:
    - One ‘u’ is seen for a ‘e’
    - Result is poor because pattern is small

Image and search pattern

Add border to search pattern



Correlate image with search pattern



Threshold on peaks of correlation



Map search result on original image



Calculation of sharpness in the image

Frequencies increase from the origin



Idea: calculate the energy in the higher frequencies

27-aug-18 Fourier Transform 77

In focus value

InFocusValue (image, lowestfreqnr)

This operator calculates a value for how good the image is in focus (='sharpness'). The higher the returned value the more high frequencies are present in the image.

The parameter lowestfreqnr specifies the lowest frequency nr in the FT which is used in the calculation.

27-aug-18 Fourier Transform 78

Demonstration In focus value

- Apply operator InFocusValue on the images with lowestFreqNr = 20:
  - (show results in server log)
  - Plate_m1.jl (before focus)
  - Plate_0.jl (in focus)
  - Plate_p1.jl (after focus)

27-aug-18 Fourier Transform 79

Demonstration In focus value



27-aug-18 Fourier Transform 80

Exercise sharpness calculation

Make a script in order to calculate the sharpness in an image.
Use the following images to test the script:

- **Plate_m1.jl (before focus)**
- **Plate_0.jl (in focus)**
- **Plate_p1.jl (after focus)**

Modify the script in order to shoot continuously image with the camera and display for each image its sharpness

Answer first part: sharpness.jls