



Computer Vision

Hyperspectral Imaging (HSI) (Operators, first draft)

27 August 2018

Copyright © 2001 – 2018 by
NHL Stenden Hogeschool and Van de Loosdrecht Machine Vision BV
All rights reserved

j.van.de.loosdrecht@nhl.nl, jaap@vdlmv.nl

Hyperspectral Imaging operators overview

Overview:

- 3 types of Hyperspectral images in VisionLab
- Demo basic HSI operators
- Normalized Difference Vegetation Index (NDVI)
- Noise correction by Flat Field Correction (FFC)
- Exercise Flat Field Correction Line
- Analyse bands FX17 using 1st and 2nd derivative
- Short description of all Multi-Channel (MC) image operators

28-aug-18

HSI operators

2

VisionLab supports 3 types of Hyperspectrale Images

- **Multi-Channel (MC) images:** The pixels are stored in memory in lines of MCPixels. Within one MCPixel the channels are sequential stored. This is the basic HSI type in VisionLab, this format is used by many MC operators. All pixels are stored in one image.
- **Raw or Mosaic images:** These are the raw images typically produced by hyperspectral area scan cameras. All pixels are stored in one images.
- **Band images:** Each channel (band) is stored in a separated image. The channels are "bundled" in an array script variable with in the array elements the names of the band images.

28-aug-18

HSI operators

3

Multi-Channel (MC) image operators

- | | |
|---------------------|-----------------|
| • MCViewer | • MCMerge |
| • MosaicViewer | • MCNVDI |
| • BandViewer | • MC(I)ReadENVI |
| • MC1stDerivative | • MCReorder |
| • MC2ndDerivative | • MCROI |
| • MCCloneNrChans | • MCROI2Points |
| • MCContrastStretch | • MCSelectRange |
| • MCConvert | • MCSelectChans |
| • MCFromBIL | • MCSetChan |
| • MCFromBands | • MCSetChans |
| • MCFromDemosaic | • MCSetNrChans |
| • MCGetChan | • MCTile |
| • MCGetChans | • MCTranspose |
| • MCGetNrChans | • MCZoom |
| • MCGetPixel | • MCZoomXY |
| • MCGetHeightWidth | |

28-aug-18


HSI operators

4

Example HSI MCFA camera, 9 bands



CMS-V 550-830nm



Source: www.silios.com/cms-cameras-1

28-aug-18

HSI operators

5

Silios CMS-V specs

FILTER SPECIFICATIONS	
Macro-pixel size	3x3 bands
Wavelength range	550 to 800 nm typical
Type of pixel	8 colors (narrow bands) + 1 B&W
Band 1	λ_c : 553 nm / FWHM : 30 nm / T_{max} : 57%
Band 2	λ_c : 587 nm / FWHM : 29 nm / T_{max} : 58%
Band 3	λ_c : 629 nm / FWHM : 28 nm / T_{max} : 57%
Band 4	λ_c : 665 nm / FWHM : 27 nm / T_{max} : 57%
Band 5	λ_c : 714 nm / FWHM : 26 nm / T_{max} : 54%
Band 6	λ_c : 749 nm / FWHM : 25 nm / T_{max} : 53%
Band 7	λ_c : 791 nm / FWHM : 25 nm / T_{max} : 50%
Band 8	λ_c : 829 nm / FWHM : 27 nm / T_{max} : 48%
Band 9	Neutral density : T_{mean} = 9% over [500-900] nm

28-aug-18

HSI operators

6

Demo basic MC image operators

- Open file with MC image tomatos-Silios-VIS.jl
- Convert to Multi-Channel format with Demosaic image 3 3
- Look at Image Attributes (F11) for channel info
- Options setting MC Display (OneChan or Raw) govern the way MC images are displayed
- MC Pixel layout in Raw view on MC image
- MC Viewer, scroll in bands, adjust Gamma, extract one band
- MCROI image 50 50 100 200
- MCROI2Points LineTool height = width = 0
- MCROI2Points LineTool height & width != 0
- MCTile 3 3
- Extract Band Images with MCGetChans &\$allBands (with &)
- Band Viewer \$allBands (without &)
- MCReorder image (8,2,1,0,6,3,4,5,7)
- View bands and observe expected darker -> brighter for plants

28-aug-18

HSI operators

7

Hyperspectral mosaic image




28-aug-18

HSI operators

8

Convert to Multi-Channel format




28-aug-18

HSI operators

9

Converted to Multi-Channel format



28-aug-18

HSI operators


10



- **OneChan:** one channel of MC image is displayed, channel chosen is specified with Options MC Gray Mapping parameter
- **Raw:** the MC image is displayed as lines of MCPixels. Within one MCPixel the channels are sequential displayed. The raw image has the normal height, but the width is normal width * number of channels.

12

MC Display = GrayScale, MC Gray Mapping = channel 4




28-aug-18

HSI operators

13

MC Display = Raw (MC Gray Mapping = don't care)



28-aug-18

HSI operators

14

First MCpixel at left-top

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
0	3163	3136	3087	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271	3271
1	3263	3243	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
2	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267	3267
3	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
4	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
5	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
6	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
7	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
8	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
9	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
10	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
11	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263
12	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263	3263

28-aug-18HSI operators15

Alternative use MC image attributes nrChans ...

Image Attributes

Name: tomato-silos-VIS.tif/3

Type: Int16Image

LUT: Stretch

Connected: NotConnected

Print scale: 10

nrChans: 1

nrChannels: 1

nrChannels: 1

History

tomato-silos-VIS.tif/2

vc1readread tomato-silos-VIS.tif/2

MCFromDemosaic tomato-silos-VIS.tif/2 tomato-silos-VIS.tif/3 3 3

Print image and history


Image to clipboard

Ok

Cancel


28-aug-18HSI operators16

.. to see raw view on MC image




28-aug-18 HSI operators 17

MC Viewer, band 0




28-aug-18 HSI operators 18

MC Viewer, band 4




28-aug-18 HSI operators 19

Extract band 4



28-aug-18 HSI operators 20



Multi-Channel ROloperators

- **MCROI** srcImage destImage x y height width
The MCROI operator copies the ROI specified by x, y, height and width in the MC srcImage to the MC dstImage.
Note that x, y, height and width are defined for MC pixels.
- **MCROI2Points** srcImage destImage leftTop rightBottom height width
This operator is intended to be used with the LineTool widget.
The MCROI2Points operator copies a ROI rectangle in the MC srcImage to the MC dstImage.
If height = 0 the rectangle is defined by the leftTop and rightBottom coordinates.
If height != 0 the rectangle is defined by the leftTop coordinate, height and width.
Note that leftTop and rightBottom coordinates, height and width are defined for MC pixels.

28-aug-18

HSI operators

22

MCROI

x, y, height and width are defined for MC pixels

28-aug-18

HSI operators

23

MCROI

Result ROI with MCImage

Image Attributes

Name

tomato-siloes-VIS_jf68

mChars

9

Type

mImage

Height*Width

131x173

LUT

Stretch

Reduce

1

Connected

NotConnected

Print scale

10

History

tomato-siloes-VIS_jf62
xIdentified tomato-siloes-VIS_jf62
MCFromDemosaic tomato-siloes-VIS_jf62 tomato-siloes-VIS_jf63 3 3
MCROIPoints tomato-siloes-VIS_jf63 tomato-siloes-VIS_jf68 (65,50) (2


Print image and history

Image to clipboard

Jaap van de Loosdrecht, NHL, vdLMV, j.van.de.loosdrecht@nhl.nl

12

Use menu Operator | Widget Tools | MCROI2Points
to select leftTop and rightBottom of rectangle




The screenshot shows the VisionLab V3.46 software interface. On the left is a menu bar with 'Operator' selected. Below it is a list of operators including 'Threshold Tool', 'Threshold', 'Threshold auData', 'Remove Blobs', 'Remove Border Blobs', 'Label Blobs', 'Blob Analysis', 'Grayscale Blob Analysis', 'Remove Labels', 'Add', 'Subtract', 'And', 'Or', 'ExOr', 'Convolution', 'ROI', 'Sobel', 'Erosion', 'Dilation', 'Opening', and 'Closing'. The main window displays a grayscale image of a tomato plant with a blue rectangle overlaid. A small dialog box titled 'tomato-silos-VIS_jf%3 (MC int16Image Stretch) Ra 1' is open over the image. At the bottom, a status bar shows 'Server log disabled'.

28-aug-18

HSI operators

25

Select MCROI2Points operator
(note: height = width = 0)



The screenshot shows the VisionLab V3.46 software interface with the 'MCROI2Points' dialog box open. The dialog box has fields for 'src' (tomato-silos-VIS_jf%3), 'dest' (tomato-silos-VIS_jf%6), 'leftTop' (0,50), 'rightBottom' (252,180), 'height' (0), and 'width' (0). There is a 'Cancel' button at the bottom right of the dialog. The background shows the same tomato plant image with a blue rectangle as in the previous slide.



28-aug-18

HSI operators


26

Jaap van de Loosdrecht, NHL, vdLMV, j.van.de.loosdrecht@nhl.nl


13




Result MCROI2Points defined by leftTop, height and width



MCTile operator




Result MCTile




28-aug-18HSI operators31

Extract all channels in "bundled" array script variable



28-aug-18HSI operators32

Variable array \$allBands contains names of all images
<imageName>-bandNr



The screenshot shows the VisionLab V3.46 software interface. On the left is a menu bar with options like Open, Save, New Script, etc. The main window displays a grayscale image of a tomato. Overlaid on this is a 'Variables' window. Inside this window, the variable '\$allBands' is defined as an array of strings: 'tomato-silos-VIS_jf54_0', 'tomato-silos-VIS_jf54_1', 'tomato-silos-VIS_jf54_2', and 'tomato-silos-VIS_jf54_3'. The array is displayed in a table with 'index' and 'value' columns.


index	value
0	tomato-silos-VIS_jf54_0
1	tomato-silos-VIS_jf54_1
2	tomato-silos-VIS_jf54_2
3	tomato-silos-VIS_jf54_3

28-aug-18

HSI operators

33

Variable array \$allBands contains names of all images
<imageName>-bandNr



This screenshot shows the same VisionLab V3.46 interface, but with a 'List of images on server' dialog box open. The dialog box contains a list of image names and their dimensions (341x426). The list includes 'tomato-silos-VIS_jf54_0.tif', 'tomato-silos-VIS_jf54_1.tif', 'tomato-silos-VIS_jf54_2.tif', 'tomato-silos-VIS_jf54_3.tif', 'tomato-silos-VIS_jf54_4.tif', 'tomato-silos-VIS_jf54_5.tif', 'tomato-silos-VIS_jf54_6.tif', 'tomato-silos-VIS_jf54_7.tif', and 'tomato-silos-VIS_jf54_8.tif'. Buttons for 'Display', 'Delete', 'DeleteAll', and 'Cancel' are visible on the right side of the dialog.

28-aug-18

HSI operators

34

Ordering of channels within MCPixel

According to Silios specifications the channels (bandnr -1) are ordered in the mosaic sensor:

3	2	1
5	6	7
4	8	0

In VisionLab channels for a 3x3 mosaic are ordered:

0	1	2
3	4	5
6	7	8

28-aug-18

HSI operators

35

MReorder operator

MReorder srcImage destImage orderList

Menu: Operator | HSI

The MReorder operator copies the MC srcImage to the MC destImage and reorder the channels in the MC destination pixel according to orderList. The orderList is specified as a tuple with the desired channel order of the new channels using the channel numbers of the original image.

28-aug-18

HSI operators

36

Ordering of channels within MCPixel

According to Silios specifications the channels (bandnr -1) are ordered in the mosaic sensor:

3	2	1
5	6	7
4	8	0

Order list:
(8,2,1,0,6,3,4,5,7)
chan 8 -> chan 0
chan 2 -> chan 1
etc.

In VisionLab channels for a 3x3 mosaic are ordered:


0	1	2
3	4	5
6	7	8

28-aug-18

HSI operators

37

Reorder channels in order of longer wave lengths




28-aug-18

HSI operators

38

Browse through channels will give expected behaviour of healthy plant



28-aug-18

HSI operators

39

View 3 channels in false colors

Note all operators can be found in menu HSI

- Open image tomato-silios-VIS.jl
- MCFromDemosaic image 3 3
- MCReorder image (8,2,1,0,6,3,4,5,7)
- MCSelectChans image (0,4,7)
- MCContrastStretch image (0,0,0) (255,255,255)
- MCConvert image RGB888Image

28-aug-18

HSI operators

40


Select 3 of the 9 channels

28-aug-18HSI operators41

3 channels selected

28-aug-18HSI operators42

Contrast Stretch all 3 channels to range for RGB888




28-aug-18

HSI operators

43

Convert to RGB888




28-aug-18

HSI operators

44

Result in false colors




28-aug-18

HSI operators


45

Normalized Difference Vegetation Index (NDVI)

NDVI = (NIR – Red) / (NIR + Red)



Why do plants reflect lots of infrared light?



FILTER SPECIFICATIONS

Macro-pixel size	3x3 bands
Wavelength range	550 to 800 nm typical
Type of pixel	8 colors (narrow bands) + 1 B&W
Band 1	λc : 553 nm / FWHM : 30 nm / T _{max} : 57%
Band 2	λc : 587 nm / FWHM : 29 nm / T _{max} : 58%
Band 3	λc : 629 nm / FWHM : 28 nm / T _{max} : 57%
Band 4	λc : 665 nm / FWHM : 27 nm / T _{max} : 57%
Band 5	λc : 714 nm / FWHM : 26 nm / T _{max} : 54%
Band 6	λc : 749 nm / FWHM : 25 nm / T _{max} : 53%
Band 7	λc : 791 nm / FWHM : 25 nm / T _{max} : 50%
Band 8	λc : 829 nm / FWHM : 27 nm / T _{max} : 48%
Band 9	Neutral density : T _{transp} = 9% over [500-900] nm

Select band 4 and band 8

Note in mosaic channel nr starts at 0

- band 4 = chan^s 3 = chan^{vl} 0 (red)
- band 8 = chan^s 7 = chan^{vl} 5 (nir)

Silios chans	VisionLab chans																		
<table><tr><td>3</td><td>2</td><td>1</td></tr><tr><td>5</td><td>6</td><td>7</td></tr><tr><td>4</td><td>8</td><td>0</td></tr></table>	3	2	1	5	6	7	4	8	0	<table><tr><td>0</td><td>1</td><td>2</td></tr><tr><td>3</td><td>4</td><td>5</td></tr><tr><td>6</td><td>7</td><td>8</td></tr></table>	0	1	2	3	4	5	6	7	8
3	2	1																	
5	6	7																	
4	8	0																	
0	1	2																	
3	4	5																	
6	7	8																	

28-aug-18

HSI operators

46

Demo Normalized Difference Vegetation Index (NDVI)


- Open file with MC image Silios-potato-field.jl
- Demosaic image 3 3
- MCNDVI image 5 8
- Open file BlueGreen256LUT.jl for LUT
- Select RangeToFalseColor operator from Color menu
RangeToFalseColor image lut (2nd select) 0 0.3

28-aug-18

HSI operators

47



Open file Silios-potato-field.jl




28-aug-18

HSI operators

48



Floating point image result of MCNDVI operator




28-aug-18

HSI operators

51

Floating point image result of MCNDVI operator



28-aug-18

HSI operators

52

Open BlueGreen256LUT.jl

0 us

28-aug-18

HSI operators

53

File

Operator

Camera

Server

Options

Window

OpenCL

User1

User2

User3

VegetationIndex

Help

Open

Save

New Script

Close All

Select 2nd

Exit

Pixels

Histogram

Snapshot

Setup

Ext

Threshold Tool

Threshold

Threshold IsoData

Remove Blobs

Remove Border Blobs

Label Blobs

Blob Analysis

Grayscale Blob Analysis

Remove Labels

Add

Subtract

And

Or

ExOr

Convolution

ROI

Sobel

Erosion

Dilation

Opening

Closing

0 us

28-aug-18

HSI operators

53

0 us

28-aug-18

HSI operators

53

Select RangeToFalseColor operator from Color menu

0 us

28-aug-18

HSI operators

54

File

Operator

Camera

Server

Options

Window

OpenCL

User1

User2

User3

VegetationIndex

Help

Open

Save

New Script

Close All

Select 2nd

Exit

Pixels

Histogram

Snapshot

Setup

Ext

Threshold Tool

Threshold

Threshold IsoData

Remove Blobs

Remove Border Blobs

Label Blobs

Blob Analysis

Grayscale Blob Analysis

Remove Labels

Add

Subtract

And

Or

ExOr

Convolution

ROI

Sobel

Erosion

Dilation

Opening

Closing

0 us

28-aug-18

HSI operators

54

0 us

28-aug-18

HSI operators

54

NDVI in false colors

28-aug-18

HSI operators

55

Single camera multi shot Push-broom scanner

Specim FX10 VIS/NIR, 400 - 1000 nm, 224 bands
Specim FX17 NIR/SWIR, 900 - 1700 nm, 224 bands

28-aug-18

Hyperspectral Imaging

56

Hyperspectral linescan camera

Transparent plastic sorting

In collaboration with NHL Stenden Lectoraat Circular Plastics




28-aug-18

Hyperspectral Imaging

57

Chemical finger printing Application plastic sorting

The SWIR absorbance depends on the type of polymer



28-aug-18


Hyperspectral Imaging

58


Flat Field Correction

$$C = \frac{R - D}{B - D}$$

R = Raw
C = Corrected
B = Brightfield
D = Darkfield




R




28-aug-18

B




D



HSI operators

C



59

Demo noise correction by Flat Field Correction (FFC) part 1

- Open ENVI file Plastic.raw (must use local VisionLab server)
- Image Attributes (menu Operator | Analyses) shows 224 bands
- Examen image with MCViewer, change gamma to 0.25
browse through bands, note noise in lower and high 10 bands
- Open DARKREF.raw and WHITEREF.raw
- Use FlatFieldLine (menu Operator | Point) to generate single line DarkRef and WhiteRef images
- Because FlatFieldLine is not an MC operator, use Image Attributes of DarkRef and WhiteRef to set NrChans to 224
- Apply Flat Field Correction Line (menu Operator | Point) to plastic image using DarkRef as 2nd and WhiteRef as 3rd image
- Because Flat Field Correction Line is not an MC operator, set result image NrChans to 224

28-aug-18

HSI operators

60


Demo noise correction by Flat Field Correction (FFC) part 2

- **Note: results looks brighter because result is FloatImage, which has default display LUT FloatLog**
- **Use Image Attributes to change LUT to FloatLinear, examen result with MCViewer and gamma = 0.25**
Note noise reduced in lower and high 10 bands and compare with original image

28-aug-18

HSI operators

61


Open ENVI file Plastic.raw

28-aug-18

HSI operators


62

Image attributes: set nrChans to 224 channels




28-aug-18HSI operators63

Adjust Gamma to 0.25
The first and last 10 channels contain a large amount of noise



28-aug-18HSI operators64

Browse through channels to see spectral response




28-aug-18

HSI operators

65

Open White and Dark reference images



28-aug-18

HSI operators

66

Flat Field (Correction) Line operators


These operators are used to perform a Flat Field Correction for line-scan images

FlatFieldLine image flatfield
FlatFieldCorrectionLine raw dark bright corrected


Class: ordImage, see Image hierarchy overview
Menu: Operator | Point

The operator FlatFieldLine generates from a reference image (dark field or bright field) an averaged flat field image of height 1
The operator FlatFieldCorrectionLine performs the Flat Field correction based on darkfield image dark and brightfield image bright and produces the corrected image


FlatFieldLine (menu Operator | Point)



Examen both results




Because FlatFieldLine is not an MC operator, use Image Attributes of DarkRef and WhiteRef to set nrChans to 224



Flat Field Correction Line

Select Dark as 2nd and White as 3rd image




28-aug-18

HSI operators

71

Examen result FFC and set nrChans to 224




28-aug-18

HSI operators

72

Examen result FFC




Note: results looks brighter because result is FloatImage, which has default display LUT FloatLog

28-aug-18

HSI operators

73

Set displayLut to FloatLinear




28-aug-18

HSI operators

74

Examen result




28-aug-18

HSI operators

75

Browse through bands with MCViewer
Note noise reduced in lower and high 10 bands



28-aug-18

HSI operators

76

Exercise Flat Field Correction Line

Write a script that performs a FFCLine on image Plastics.raw using Dark.raw and White.raw using only the basic Image Math operators and operators like SumColumns and ExtendBorder

**Use script FlatFieldCorrPlastics.jls in exercises as framework. This contains a regression test to test the result
The resulted image should have the name CorEx**

See FlatFieldCorrPlastics.jls in answers directory for answer

28-aug-18

HSI operators

77

Demo analyse bands FX17

Run script FFC-Plastics.jls

- FFC Plastics and convert to Int16Image
- Extract one column with MCPixels
- Use Analyse Pixels (F11) to examine the bands in horizontal pixels
- Calculate 1st and 2nd derivative of MCPixels
- Exam the bands in 1st derivative
- Exam the bands in 2nd derivative
- Calculate 2nd derivatives for high 1st derivatives
- Exam 2nd derivatives for high 1st derivatives

28-aug-18

HSI operators

78

script FFC-Plastics.jls

```
// FFC-Plastics.jls
// Flat Field Correction on plastics
// 6-7-2018 Jaap van de Loosdrecht

MCReadENVI org Plastics.raw
MCReadENVI dark DARKREF.raw
MCReadENVI white WHITEREF.raw

FlatFieldLine dark darkLine
FlatFieldLine white whiteLine
FlatFieldCorrectionLine org darkLine whiteLine ffc_f
MultiplyPixel ffc_f 500
Convert ffc_f ffc Int16Image
MCCloneNrChans org ffc
Display ffc

MCROI ffc roi 269 0 1255 1
MCSetNrChans roi 1
Display roi
```

```
// 2nd part

MC1stDerivative ffc D1
MC2ndDerivative ffc D2
MCROI D1 D1roi 269 0 1255 1
MCROI D2 D2roi 269 0 1255 1
MCSetNrChans D1roi 1
MCSetNrChans D2roi 1
Display D1roi
Display D2roi


Copy D1roi D1roiThres
threshold D1roiThres 5 1000
Copy D1roi D1roiHigh
Abs D1roi
Multiply D1roiHigh D1roiThres
Copy D2roi D2roiMax
Multiply D2roiMax D1roiHigh
Display D2roiMax
```

28-aug-18

HSI operators

79

FFC Plastics and convert to Int16Image




28-aug-18

HSI operators


80

Extract one column with MCPixels




28-aug-18 HSI operators 81

Use Analyse Pixels (F11) to examine the bands in horizontal pixels



28-aug-18 HSI operators 82

Calculate 1st and 2nd derivative of MCPixels



```
Convert ffc_f ffc Int16Image
MCCloneMcChans org ffc
Display ffc
break

MCRoi ffc roi 269 0 1255 1
MCSetMcChans roi 1
Display roi
break


MC1stDerivative ffc D1
MC2ndDerivative ffc D2
MCRoi D1 D1roi 269 0 1255 1
MCRoi D2 D2roi 269 0 1255 1
MCSetMcChans D1roi 1
MCSetMcChans D2roi 1
Display D1roi
Display D2roi
break
```

28-aug-18

HSI operators

83

Exam the bands in 1st derivative



Coordinates: X: 90, Y: 296, Pixel value: -25

Horizontal pixels: [Plot showing pixel values vs. horizontal index]


Vertical pixels: [Plot showing pixel values vs. vertical index]

28-aug-18

HSI operators

84

Exam the bands in 2nd derivative




28-aug-18

HSI operators

85

Calculate 2nd derivatives for high 1st derivatives




28-aug-18

HSI operators

86

Exam 2nd derivatives for high 1st derivatives



Multi-Channel (MC) image operators

All MC operators can be found in menu Operator | HSI

- **MCViewer**
With this form a Multi Channel image can be inspected. With the Channel scroll bar the channel to be inspected can be chosen. The contrast in the displayed channel can be adapted with the Gamma scroll bar.
- **MosaicViewer**
With this form a Raw mosaic image can be inspected. The number of horizontal and vertical pixels in one MCPixel must be specified.
With the Channel scroll bar the channel to be inspected can be chosen. The contrast in the displayed channel can be adapted with the Gamma scroll bar.

28-aug-18

HSI operators

88

Multi-Channel (MC) image operators

- **BandViewer**
With this form a Band image can be inspected.
The array script variable with in the array elements the names of the band images must be specified.
With the Channel scroll bar the channel to be inspected can be chosen. The contrast in the displayed channel can be adapted with the Gamma scroll bar.
- **MC1stDerivative srcImage destImage**
The MC1stDerivative operator calculates for each MCPixel in the srcImage the first derivative and stores this in the destImage.

28-aug-18

HSI operators

89

Multi-Channel (MC) image operators

- **MC2ndDerivative srcImage destImage**
The MC2ndDerivative operator calculates for each MCPixel in the srcImage the second derivative and stores this in the destImage.
- **MCCloneNrChans srcImage destImage**
The operator MCCloneNrChans set the number of channels of the MC srcImage to the MC destImage.
This operators is commonly used after a non-MC operator is applied to a MC image that results in new image.
The new image will have its nrChans attribute set to 1. If the new image is to be used as MC image, nrChan has to be set to the correct value.

28-aug-18

HSI operators

90

Multi-Channel (MC) image operators

- **MCContrastStretch image low high**
The operator MCContrastStretch will stretch the contrast in all channels of the MC image.
The parameters low and high contain tuples with the low and high boundaries for the stretch. Note all channels will be stretched individually.

Example for image mc with 3 channels:|
MCContrastStretch mc (0,0,0) (255,255,255)
- **MCConvert srcImage destImage imageType**
The operator MCConvert converts the srcImage to a destImage of the specified imageType.

28-aug-18

HSI operators

91

Multi-Channel (MC) image operators

- **MCFFromBIL BIL_image MC_image nrBands**
The MCFFromBIL operator creates a MC image from an image with BIL (Band Interleaved by Line) format.
The number of bands in the BIL image has to be specified.
- **MCFFromBands image &\$imageTab**
The MCFFromBands operator creates a MC image using the specified band image with the array variable imageTab.
Note: the array variable name should be specified with &\$, example: &\$imageTab.

28-aug-18

HSI operators

92

Multi-Channel (MC) image operators

- **MCFromDemosaic srcImage destImage nrHBands nrVBands**
The operator **MCFromDemosaic** converts the raw mosaic **srcImage** to a MC **destImage**. The number of horizontal and vertical bands in the mosaic are specified with **nrHBands** and **nrVBands**.
- **MCGetChan image channellImage chanNr**
The **MCGetChan** operator copies the channel **chanNR** in MC image to specified **channellImage**.
- **MCGetChans image &\$imageTab**
The **MCGetChans** operator converts the specified MC image to a band image specified with the array variable **imageTab**.
Note: the array variable name should be specified with **&\$**, example: **&\$imageTab**.

28-aug-18

HSI operators

93

Multi-Channel (MC) image operators

- **MCGetNrChans image**
The **MCGetNrChans** returns the number of channels of the MC image.
- **MCGetPixel image pixel x y**
The **MCGetPixel** operator selects the MC pixel at position (x,y) and convert it to an image with name **pixel**.
- **MCGetHeightWidth image**
The **MCGetHeightWidth** operator returns the tuple (height,width) of the MC image in MC pixels.

28-aug-18

HSI operators

94

Multi-Channel (MC) image operators

- **MCMerge src1Image src2Image destImage**
The **MCMerge** operator merges the channel of two MC source images into the MC destination images.
The source images should have the same height and width in MC pixels.
- **MCNVDI srcImage destImage nirBand visBand**
The **MCNVDI** calculated the Normalized Difference Vegetation Index in the MC src image using the specified nirBand and visBand.
The result is stored in destImage of type FloatImage.

28-aug-18

HSI operators

95

Multi-Channel (MC) image operators

- **MCReadENVI imageName filename**
The ENVI file with fileName is read and added to the server with imageName.
Note that one ENVI file "comes in pairs", one file with extension .raw and one file with extension .hdr .
The .raw or .hdr file must be specified as fileName.
ReadENVI uses file path of server, MCReadENVI file path of client.
Note: not all sub-types of the ENVI are supported. No support yet for Write_ENVI.

28-aug-18

HSI operators

96

Multi-Channel (MC) image operators

- **MCREorder srcImage destImage orderList**
The MCREorder operator copies the MC srcImage to the MC destImage and reorder the channels in the MC destination pixel according to orderList.
The orderList is specified as a tuple with the desired channel order of the new channels using the channel numbers of the original image.
Example for an MC image with 25 channels:
(1,0,3,2,5,4,7,6,9,8,11,10,13,12,15,14,17,16,19,18,21,20,23,22,24)

28-aug-18

HSI operators

97

Multi-Channel (MC) image operators

- **MCROI srcImage destImage x y height width**
The MCROI operator copies the ROI specified by x, y, height and width in the MC srcImage to the MC dstImage.
Note that x, y, height and width are defined for MC pixels.
- **MCROI2Points srcImage destImage leftTop rightBottom height width**
This operator is intended to be used with the LineTool widget.
The MCROI2Points operator copies a ROI rectangle in the MC srcImage to the MC dstImage.
If height = 0 the rectangle is defined by the leftTop and rightBottom coordinates.
If height != 0 the rectangle is defined by the leftTop coordinate, height and width.
Note that leftTop and rightBottom coordinates, height and width are defined for MC pixels.

28-aug-18

HSI operators

98

Multi-Channel (MC) image operators

- **MCSelectChans srcImage destImage (c1,...,cn)**
The MCSelectChans operator copies the specified channels MC srcImage to MC destImage.
Note that the selected channels are specified as a vector with no spaces in the string.
- **MCSelectRange srcImage destImage first last**
The MCSelectRange operator copies the range of channel between first and last of MC srcImage to MC destImage.
Note that the selected channels are specified as a vector with no spaces in the string.

28-aug-18

HSI operators

99

Multi-Channel (MC) image operators

- **MCSetChan image channellImage chanNr**
The MCSetChan operator replaces channel chanNR in MC image with specified channellImage.
- **MCSetChans image &\$imageTab**
The MCSetChans operator converts a band image specified with the array variable imageTab to a MC image with name image.
Note: the array variable name should be specified with &\$, example: &\$imageTab.
- **MCSetNrChans image nrChans**
The MCSetNrChans operator sets the number of channels of the MC image to nrChans.

28-aug-18

HSI operators

100

Multi-Channel (MC) image operators

- **MCSetPixel image pixel x y**
The MCSetPixel operator sets the MC pixel at position (x,y) to the image with name pixel.
- **MCTile srcImage destImage nrH nrV**
The MCTile converts a MC image to an ordinary image with tiles. Each tile represents a channel. The number of horizontal tile is specified with the parameter nrH and and vertical with nrV.
- **MCTranspose srcImage destImage**
The MCTranspose operator performs a transpose operation, with respect to the multi-channel pixel, on the srcImage and stores the result in destImage.

28-aug-18

HSI operators

101

Multi-Channel (MC) image operators

- **MCZoom srcImage destImage height width interpolation**
MCZoomXY srcImage destImage factorX factorY interpolation
The MCZoom operator initialises a destination MC image by enlarging of reducing the source MC image with the specified height and width using the specified interpolation technic.
The MCZoomxy operator initialises a MC destination image by enlarging of reducing the source MC image with the specified factors for x and y direction using the specified interpolation technic.
Note: both operators have a c++ prototype with the same name MCZoom.

28-aug-18

HSI operators

102